

BID SPECIFICATIONS

New Honda Pioneer 1000-6 Deluxe Crew UTV

Specifications

Engine

- Type - 999 cc liquid cooled longitudinally mounted parallel twin four-stroke
- Bore and Stroke – 92.0 mm x 75.2 mm
- Compression Ratio – 10.0:1
- Valve Train – Unicam SOHC; four valves per cylinder
- Induction – Programmed Fuel injection system (PGM-FI); 44mm throttle body.

Drive Train

- Transmission – fully automatic Dual-Clutch Transmission (DCT)
- Driveline – direct front and rear drive shafts

Chassis Suspension Brakes

- Front Suspension – independent double wishbone; 10.5 inch travel
- Rear Suspension – Independent double wishbone; 10.0 inch travel
- Front Brake – dual 210 mm hydraulic disc
- Rear Brake – single 210 mm hydraulic disc
- Front Tire – 27 x 9 x 14
- Rear Tires – 27 x 11 x 14

Dimensions

- Length – 152.2 inches
- Width – 63.0 inches
- Height – 76.1 inches
- Wheelbase – 115.2 inches
- Bed Capacity – 1000 pounds
- Towing Capacity – 2500 pounds
- Ground Clearance – 12.6 inches
- Turning Radius – 18.7 feet
- Curb Weight – 1936 pounds
- Fuel Capacity – 7.9 gallons

Exterior Body Color

- Black or Green

Required Options

- Top
- Windshield
- 3500 pound winch (including mount)
- All installation, freight, doc fees, accessory labor shall be included in bid price
- Bid price shall include delivery to Columbiana, Alabama

Warranty

- One year included